
SUNSHINE PROPRIETARY MEDIA G2® CONTROL

The Sunshine MEDIA G2® Control offers performance and features unmatched in the industry. The sophisticated electronic control is fully programmable, and is adaptable over a wide range of filter applications.

Media Lifespan Indicator

- An audible and visual Indicator informs the user to check the media
- The lifespan value can be programmed to accommodate a range of system sizes

Programmable Output Signal

- Provides an optional flow based dry contact closure for chemical feed

Low Chemical Feed Indicator

- A visual indicator informs the user of low chemical level

No Flow Indicator

- Informs user that flow meter requires maintenance

Sophisticated Electronics

The Sunshine MEDIA G2® electronic control uses NOVRAM to retain customized settings and historical data in the event of a power interruption. A rechargeable 9-volt battery provides back up for Time of Day. Fully programmable parameters allow for flexibility across a wide range of systems and applications. Historical data, such as Peak Flow, Average Daily Water Usage, Days since Backwash, are easily accessible for diagnosing and troubleshooting the system. During normal operation the display provides immediate feedback (capacity remaining and flow rate). Cycle indicators on the faceplate allow the user to quickly view each cycle position without having to press a button.

Reliable High Performance Valve

The valve and diaphragm design provide reliable trouble-free operation. The valve body is molded in lightweight thermoplastic material, allowing for easy servicing. 2-inch inlet outlet connections long with an easy access meter assembly allow for quick installation and set-up. Excellent backwash flow capabilities allow for use on a large range of system sizes. All valve components are easily accessible for quick and trouble free servicing.

